



المملكة الأردنية الهاشمية

The Hashimite Kingdom of Jordan

## Telecommunications Regulatory Commission

Conditions and Compliance List (Requierments & Specifications)  
necessary for obtaining Type Approval for Cordless Telephone working  
on Digital Enhanced Cordless Telecommunications Technology  
(DECT).

For use within the confined Area of a building In the Frequency bands  
(1880/ 1900 MHz)

Telecommunications Regulatory Commission (TRC)

Tel. **(962-6)-5862020**  
Fax **(962-6)-5863641/42**  
P.O. Box : **850967**  
**Amman 11185 Jordan**

**Directions:**

**Seventh circle,Ibrahim El-Bajori street**

**<http://www.trc.gov.jo>**

**E-mail: [trc@trc.gov.jo](mailto:trc@trc.gov.jo)**

**[spectrum@trc.gov.jo](mailto:spectrum@trc.gov.jo)**

**<http://www.trc.gov.jo>**

**[trc@trc.gov.jo](mailto:trc@trc.gov.jo)**

**[spectrum@trc.gov.jo](mailto:spectrum@trc.gov.jo)**

## Conditions:

1. The type approval for Cordless Telephone utilizing **(DECT)** technology in Jordan is restricted to confined area of a building.
2. The effective isotropic radiated power (e.i.r.p.) out of the antenna should not exceed 10 mw.
3. Because the frequencies assigned for equipment utilizing the **(DECT)** technology are lying within the same band assigned for other applications, users of these equipment must take all the necessary precautions to not cause any harmful interference for other users of the same band, and not to demand any interference protection for their equipment.
4. Frequencies for users of equipment that utilizes the **(DECT)** technology are not assigned on individual basis (it will be shared with other users).
5. The antenna for the handportable part (CPP) shall be permanently attached. It shall not be possible to easily detach, substitute or adapt the antenna provided by the manufacturer.or attach to any out source transmission facility.
6. The maximum permissible transmission distance (Range ) from the base to portable is limited to :  
Outdoor : 300 m  
InDoor : 50 m.
7. In case of connection with licensed public telecommunications networks (PSTN, ISDN, GSM, ...etc) or any telecommunications technology aside from the (DECT System), the Cordless Telephone standards must comply with the Public networks or other telecommunications standards accredited by the TRC.

### *Note:*

*The radio wave propagation of this equipment was restricted within a confined building to grant maximum possible frequency sharing and to minimize interference.*

## Requirements:

Any party that is willing to obtain a Type Approval for Cordless Telephone utilizing the **(DECT)** technology must submit the following:

1. A certificate confirming that all the systems utilizing the **(DECT)** technology are successfully tested according to the European Telecommunications Standards Institute **(ETSI)**, especially requirement for standard number **(ETS 300 176:1992)** .
2. Submit a test report includes the following:
  - Test procedure,
  - The equipment that are used in the test,
  - Documents, certifying that the test was conducted in a recognized laboratory/ies by the Telecommunications Administration in the country where the test was conducted.
3. For connection with licensed public networks (PSTN, ISDN, GSM, ...etc) and any other telecommunications technology, a certificate/s from an internationally recognized laboratory/ies confirming that the equipment complies with the TRC requirements for other public networks, must be submitted.

## Attached Documents:

The following document/s must be attached with the Compliance list.

1. A written commitment by the laboratory where the test was conducted, confirming that the equipment are working according to the European safety requirements, specially that is concerned with the radiated power emitted from the equipment.

### Note:

- All documents must be submitted in either Arabic or English Languages.
- The TRC reserves it's right at any time to modify or to add, as it finds suitable, to the conditions, requirements and standards mentioned above.
- The original compliance list must be filled as appropriate, stamped and signed by the manufacturer.

All items in this section must be completed

**(Compliance List)**  
for

For use within the confined building  
In the frequency bands (1880-1900 MHz)

Specifications	Actual Value	Comply		Official Use Only
		Yes	No	
<b>1- RF Carrier</b>				
1880 / 1900 MHz				
<b>2- RF Carrier Stability</b>				
2-1) Radio Fixed Part (RFP)            ± 50 KHz				
2-2) Portable Part (PP) i) measurement made during            ± 100 KHz the first 1 sec of the IUT going into a transmit mode from a non-transmitting mode.				
ii) measurement made at                ± 50 KHz any other time.				
<b>3- Packet Timing Jitter</b>				
3-1) slot - slot on the same channel < ± 1 µs				
3-2) bit - to - bit in the same within ± 0.1 µs slot on the same channel				

Specifications	Actual Value	Comply		Official Use Only
		Yes	No	

4- Reference Timing Accuracy of a RFP							
4-1) Reference Timing Accuracies and Stabilities							
Type of IUT	Temperature						
	Nominal	Extreme					
Multiple channel RFP	5 ppm	10 ppm					
Single channel RFP	No Test	10 ppm					
4-2) Allowable Timing Variations							
Timing accuracy and stability (ppm)	Ranges of $t_{long}$ constituting a pass (secs)						
5	$9,99995 < t_{long} < 10,00005$						
10	$9,99990 < t_{long} < 10,00010$						
5- Transmitted Power							
10 mw							
6- RF Carrier Modulation							
Peak Frequency Deviation							
Part 1 $> \pm 259 \text{ kHz} < \pm 403 \text{ kHz}$							
Part 2 $> \pm 202 \text{ kHz} < \pm 403 \text{ kHz}$							
Part 3 $> \pm 202 \text{ kHz} < \pm 403 \text{ kHz}$							
Part 4 not $> 13 \text{ kHz/ms}$							

Specifications	Actual Value	Comply		Official Use Only										
		Yes	No											
<b>7- Emission</b>														
<p>7-1 Emissions due to modulation Shall not be greater than the power levels stated below :</p> <table border="1"> <thead> <tr> <th>Emissions on RF Channel "Em"</th> <th>Max Power Level</th> </tr> </thead> <tbody> <tr> <td>Em = M ± 1</td> <td>160 µW</td> </tr> <tr> <td>Em = M ± 2</td> <td>1 µW</td> </tr> <tr> <td>Em = any other DECT channel</td> <td>20 nW*</td> </tr> </tbody> </table> <p>* NOTE : For " Em" = any other DECT channel", the max power level shall be less than 20 nW except for one instance of a 500 nW signal.</p> <p>"M" is the IUT transmit channel and "Em " is a legal DECT channel other than the IUT transmit channel.</p>	Emissions on RF Channel "Em"	Max Power Level	Em = M ± 1	160 µW	Em = M ± 2	1 µW	Em = any other DECT channel	20 nW*						
Emissions on RF Channel "Em"	Max Power Level													
Em = M ± 1	160 µW													
Em = M ± 2	1 µW													
Em = any other DECT channel	20 nW*													
<p>7-2- Emissions due to transmitter transients Shall not be greater than the power levels stated below :</p> <table border="1"> <thead> <tr> <th>Emissions on RF channel "Em"</th> <th>Max peak power level</th> </tr> </thead> <tbody> <tr> <td>Em = M ± 1</td> <td>250 µW</td> </tr> <tr> <td>Em = M ± 2</td> <td>40 µW</td> </tr> <tr> <td>Em = M ± 3</td> <td>4 µW</td> </tr> <tr> <td>Em = any other DECT channel</td> <td>1 µW</td> </tr> </tbody> </table> <p>"M" is the IUT transmit channel " Em " is a legal DECT channel other than the IUT transmit channel</p>	Emissions on RF channel "Em"	Max peak power level	Em = M ± 1	250 µW	Em = M ± 2	40 µW	Em = M ± 3	4 µW	Em = any other DECT channel	1 µW				
Emissions on RF channel "Em"	Max peak power level													
Em = M ± 1	250 µW													
Em = M ± 2	40 µW													
Em = M ± 3	4 µW													
Em = any other DECT channel	1 µW													
7-3 ) Emissions due to intermodulation not > 1 µW on all measurement channels														

Specifications	Actual Value	Comply		Official Use Only
		Yes	No	
<b>8- Transmission</b>				
<p>8-1 ) Out of band emissions when transmitting            Spurious emissions : - radiated            - conducted</p> <p>i) Freq below 1 GHz &lt; 250 nW            ii) Freq above 1 GHz &lt; 1 μW</p> <p>Peak Power Level*</p> <p>47 - 74 MHz ]            87.5 - 108 MHz ] &lt; 20 nW            108 - 118 MHz ] (for a 100 kHz            174 - 230 MHz ] measuring            bandwidth)            470 - 862 MHz ]</p> <p>* except 2 instances of a continuous-wave spurious signal for PPs for which the total peak power level shall be less than 250 nW as measured in a 3 MHz measurement bandwidth.</p>				
<b>9- Receiver</b>				
<p>9-1) Radio Receiver Sensitivity</p> <p>Bit Error Rate (BER) ≤ 0.001</p>				
<p>9-2 ) Radio Receiver irreducible bit error rate</p> <p>Bit Error Rate (BER) ≤ 0.00001</p>				
<p>9- 3) Radio Receiver interference performance</p> <p>Bit Error Rate (BER) ≤ 0.001</p>				
<p>9-4) Receiver intermodulation performance</p> <p>Bit Error Rate (BER) &lt; 0.01</p>				
<p>9-5) Spurious emissions when receiving or idling</p> <p>i) Outside the DECT band</p> <p>30 MHz - 1 GHz &lt; 2 nW            1 GHz - 12.75 GHz &lt; 20 nW</p> <p>ii) Inside the DECT band</p> <p>&lt; 2 nW in a 1 MHz bandwidth*</p> <p>* exceptions :</p> <p>1) in one 1 MHz band within the DECT freq band, the max allowable ERP shall be 20nW.            2) in up to two bands of 30 kHz, the max ERP shall be less than 250 nw.</p>				

Specifications	Actual Value	Comply		Official Use Only						
		Yes	No							
<b>Synchronization</b>										
9-6) Voltage levels CCITT REC V.11 [29]										
<b>10- Distortion</b>										
10-1 ) PP loudness rating  Sending Loudness Rating (SLR <sub>H</sub> ) = 7 dB ± 3 dB Receiving Loudness Rating (RLR <sub>H</sub> ) = 3 dB ± 3dB										
10-2) Stability loss - fixed geometry Attenuation from the digital input to the digital output shall be at least 6 dB at all freq in the range of 200 Hz to 4000 Hz										
10-3) Stability loss variable geometry  Attenuation from the digital input to the digital output shall be at least 6 dB at all freq in the range of 200 Hz to 4000 Hz										
10-4) Sending distortion  Ratio of signal to total distortion (harmonic and quantising) measured at the line interface shall not be less than 35 dB										
10-5) Receiving distortion  Ratio of signal to total distortion (harmonic and quantising) measured at the ERP shall not be less than 35 dBb										
10-6) Side tone distortion  The third harmonic distortion generated by the PP shall not be greater than 10 %.										
<b>11- Out of band (sending)</b>										
The level of any image freq produced at the digital interface shall be below a reference level obtained at 1 kHz (-4.7dBPa at MRP) by at least the amount in dB specified in the following table <u>Discrimination levels - sending</u>										
<table border="1"> <thead> <tr> <th>Applied sine wave frequency</th> <th>Limit (minimum)</th> </tr> </thead> <tbody> <tr> <td>4.6 kHz</td> <td>30 dB</td> </tr> <tr> <td>8.0 kHz</td> <td>40 dB</td> </tr> </tbody> </table>	Applied sine wave frequency	Limit (minimum)	4.6 kHz	30 dB	8.0 kHz	40 dB				
Applied sine wave frequency	Limit (minimum)									
4.6 kHz	30 dB									
8.0 kHz	40 dB									
The limits at intermediate frequency lie on a straight line drawn between the given values on a log(frequency) - linear (dB) scale.										



<b>12- Out of band (receiving)</b>										
<p>The level of spurious out-of-band image signals in the freq range of 4.6 kHz to 8 kHz measured selectively at the ERP shall be lower than the in-band acoustic level produced by a digital signal at 1 kHz set at the level specified in the following table.</p> <p><b><u>Discrimination levels – receiving</u></b></p> <table border="1"> <thead> <tr> <th>Image signal frequency</th> <th>Equivalent input level</th> </tr> </thead> <tbody> <tr> <td>4.6 kHz</td> <td>- 35 dBm0</td> </tr> <tr> <td>8.0 kHz</td> <td>- 45 dBm0</td> </tr> </tbody> </table> <p>The limits at intermediate frequency lie on a straight line drawn between the given values on a log(frequency) - linear (dB) scale.</p>		Image signal frequency	Equivalent input level	4.6 kHz	- 35 dBm0	8.0 kHz	- 45 dBm0			
Image signal frequency	Equivalent input level									
4.6 kHz	- 35 dBm0									
8.0 kHz	- 45 dBm0									
<b>12- Noise</b>										
<p>12-1) Sending noise</p> <p>The noise produced by the apparatus in the sending direction shall not exceed - 64 dBm0</p>										
<p>12-2) Sending noise (narrow band)</p> <p>The narrow-band noise (due to TDMA) produced by the apparatus in the sending direction, and contained within any 10 Hz bandwidth between the frequency limits 300 to 3400 Hz shall not exceed - 73 dBm0.</p>										
<p>12-3) Receiving noise</p> <p>If no user-controlled receiving volume control is provided, or if it is provided, at the setting where the RLR<sub>H</sub> is equal to the nominal value, the noise produced by the apparatus and measured at the ERP shall not exceed - 57 dBPa (A).</p>										
<b>13- Sampling frequency level (receiving)</b>										
<p>The level of the 8 kHz measured selectively at the ERP shall be less than - 70 dBPa.</p>										
<b>14- Acoustic shock</b>										
<p>14-1) Continuous signal</p> <p>The sound pressure level at the ERP shall not exceed 24 dBPa (rms unweighted).</p> <p>14-2) Peak signal</p> <p>The receiving equipment shall limit the peak sound pressure at the ERP to less than 36 dBPa under any continuous or transient condition.</p>										

<b>15- Delay</b>				
<p>15-1) DECT network delay</p> <p>The sum of the delays from the MRP (Mouth Reference Point) to the digital line interface and from the digital line interface to the ERP (round-trip delay) shall not exceed 27.5 ms. If an analogue line interface is provided, the delay shall not exceed 28 ms including the A/D and D/A converters at the interface to the external network.</p>				
<p>15-2) PP (Portable Part) delay</p> <p>The sum of the delays from the MRP to the air interface and from the air interface to the ERP (Equivalent Radiated Power, round-trip delay) shall not exceed 18.5 ms. This value includes the 5 ms delay of the reference FP looping back the ADPCM digital signal towards the PP.</p>				
<p>15-3) FP (Fixed Part) delay</p> <p>The sum of the delays from the digital line interface to the air interface and from the air interface to the digital line interface (round-trip delay) shall not exceed 19 ms. This value includes the 5 ms delay of the reference PP looping back the ADPCM digital signal towards the FP.</p>				